



Hefei TNJ Chemical Industry Co.,Ltd.

D1508 Xincheng Business Center,
Qianshan Rd. Hefei 230022 China

Tel : (0086) 551 65418684

Fax: (0086) 551 65418697

Email: info@tnjchem.com


Site: www.tnjchem.com

Technical Data Sheet

2-Pyrrolidone

Product Information

Chemical Name	2-Pyrrolidone
CAS #	616-45-5
Formula	C ₄ H ₇ NO
Molecular Weight	85.1
Synonyms	Butyrolactam; G-Butyrolactam; Gamma-Butyrolactam; 2-Pyrrolidone;
Chemical Structure	



Description

2-pyrrolidone is a colorless to slightly yellow liquid above 25°C., with a faint amine odor. It is a high-polar solvent and it is miscible with water and conventional organic solvents. It is miscible with a wide variety of other solvents including water, ethanol, diethyl ether, chloroform, benzene, ethyl acetate and carbon disulfide.

Physical Properties

Melting point, °C .	23-25
Boiling range, °C	245
Density @ 20°C, g/cm ³	1.12
Flash point, °C	230 °F (110 °C)

Specification

Appearance	Colorless transparent liquid above 25°C
Assay, % min.	99.9
Water, % max.	0.10
PH(10% Solution)	8.5-10..5
Color, Hazan max	15

Safety

May cause irritation to eyes, skin and respiratory systems. Avoid contact with strong acids and oxidizing agents.

Always refer to the Material Safety Data Sheet (MSDS) for detailed information on safety

Applications

Intermediate used in/as:

- Formulation aids
- Industrial chemicals
- Initial product for chemical syntheses
- Pharmaceuticals
- Solvent for inks

Recommended Use

To produce synthetic resin

To produce pesticide

To produce polyvalent alcohol

To produce polyvinylpyrrolidone

To produce polyamide-4 fiber

To produce paracetamol

To produce printing inks and coatings

Packing

200kg per iron/HDPE drum, 16mt (80 drums) per 20ft container (20'FCL)

1000kg per IBC, 20mt (20 IBCs) per 20ft container (20'FCL)

20mt per IsoTanks

Storage & Handling

2-Pyrrolidone has a shelf life of 12 months in unopened, original containers, stored below 30° C but above 25° C. It must be protected from fire and sources of ignition. The container should be kept dry as the product is hygroscopic.

Always refer to the Material Safety Data Sheet (MSDS) for detailed information on handling and disposal.

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchant ability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall we be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if we has been advised of the possibility of such damages.